

## MP-20

### Combo Thermal Tape and Label Printer



> Good things come in small pack-

- **Thermal Dot Line Printing**
- **Fast**– Prints 20 mm per second
- **Compact**– Footprint is less than 5" x 7"
- **Light Weight**– Weighs less than 1 pound

# MP-20 Combo Thermal Tape and Label Printer

---

## Specifications

---

**Print Method**– Thermal dot line printing

**Serial Interface**– RS-232

**Baud Rate**– 9600

**Print Speed**– .79" / sec (20 mm / sec)

**Feeding Speed**– .94" / sec (24 mm / sec)

**Printing Width**– 1.89" (48 mm)

**Dots Per Line**– 384

**Dot Density**– 8 dots/mm

**Power**– DC9V / 2.8A

**Current Consumption**–

Printing: 800mA

Feeding: 300mA

Stand by: 80mA

**Operating Temp**– 32° F to 122° F (0° C to - 50° C)

**Storage Temp**– -13° F to 149° F (-25° C to 65° C)

**Dimensions**–

4.72" W x 6.69" W x 3.54" H

120 mm (W) x 170 mm (W) x 90 mm (H)

**Maximum Printable Label Size**–

1.97" W x 3.94" L

50 mm (W) x 100 mm (L)

**Weight**– Approx. 12.6 oz ( 360 g), excluding paper roll

**Error Conditions Detected**–

Paper out, Head up, Overheat



a division of Avery Weigh-Tronix, LLC

### Salter Brecknell Weighing Products

1000 Armstrong Dr., Fairmont, MN 56031

Toll free: 800-637-0529, Tel: 507-238-8702

Fax: 507-238-8271

e-mail: [sales@salterbrecknell.com](mailto:sales@salterbrecknell.com)

[www.salterbrecknell.com](http://www.salterbrecknell.com)

